


ZINC

Ribbon Anodes

CATHODIC PROTECTION FOR:
-AC Mitigation
-Bottom of Storage Tanks
-Steel Pipelines




SUPER

1" x 1-1/4" (25.4 mm x 31.7 mm)
2.4 lbs/ft (3.57 kg/m)
core dia .185" (4.7 mm)
100 ft (30.48 m) roll length
36" (0.9 m) roll ID - open coil steel banded



PLUS

5/8" x 7/8" (15.9 mm x 22.2 mm)
1.2 lbs / ft (1.8 kg / m)
core dia .135" (3.4 mm)
200 ft (60.96 m) roll length
36" (0.9) roll ID - open coil steel banded



STANDARD

1/2" x 9/16" (12.7 mm x 14.3 mm)
core dia .130" (3.3 mm)
0.6 lbs / ft (0.9 kg/m)
500 ft (152.4 m) roll length
12" (0.3 m) roll ID wood reel



SMALL

11/32" x 15/32" (8.7 mm x 11.9 mm)
core dia .115" (2.9 mm)
0.25 lbs / ft (0.4 kg/m)
1000 ft (30.48 m) roll length
12" (0.3 m) roll ID wood reel

BENEFITS

- Simple installation
- Continuous lengths
- Even current distribution
- Excellent for use in small and limited space
- Self regulating current output



www.galvotec.com

SALES OFFICE: 181 Grefer Lane • Harvey, LA 70058 USA
Tel: 504/362-7776 • Fax: 504/362-7440

CORPORATE OFFICE: McAllen, Texas USA • Tel: 956/630-3500
e-mail: anodes@galvotec.com

Galvotec™ Anodes are manufactured by Galvotec Alloys, Inc.
Galvotec™ is a trademark of Galvotec Alloys, Inc., for sacrificial anodes.
© 2006 Galvotec Alloys, Inc. All rights reserved.

GA Galvotec®